

Manufacturer/Supplier: Vandex Isoliermittel-Gesellschaft mbH, D-21493 Schwarzenbek
Product number: 05
Trade name: VANDEX BB 75
Printing date: 01.03.2000

Reviewed on: 01.03.2000

Page: 001/004

01. Identification of substance, preparation and company

Trade name

VANDEX BB 75

Manufacturer/Supplier

Vandex Isoliermittel-Gesellschaft m.b.H.

Street/P.O. Box

Industriestrasse 19 - 23

Country Code/Postal Code/Town/City

D-21493 Schwarzenbek

Telephone/Telefax

Phone: +49 4151 89 15-0

Fax: +49 4151 89 15 50

Emergency Information

Phone: +49 4151 89 15 31 (Laboratory, Vandex Isoliermittel GmbH, Germany)

Phone: +41 33 227 44 44 (Mrs. Ch. Pridal, Vandex International Ltd, Switzerland)

from 1.7.2000: +41 32 626 36 36

02. Composition/Information on components

Chemical characterization

Cement preparation

Hazardous components

Cement

Concentration: 50 - 55

Symbol: Xi

CAS number: 65997-15-1

R: 36/38-43

03. Hazards identification

Hazard designation

Xi irritant

Particular information pertaining specific risk for human an environment

R 36/38 Irritating to eyes and skin.

R 43 May cause sensitization by skin contact.

04. First aid measures

Inhalation

Take casualties away from dust polluted areas. In case of irritation of the air passages seek medical advice.

Skin contact

After contact with skin wash immediately with plenty of water. If irritation persists seek medical advice.

Eye contact

In case of contact with the eyes rinse immediately with plenty of water (eye lid wide open) for at least 10 minutes and seek medical advice.

Ingestion

Drink plenty of water. Seek medical advice.

05. Fire-fighting measures

Product is not combustible. In contact with extinguishing water an alkaline solution - which can cause irritation - is produced.

Extinguishing media - suitable

Not applicable.

Special risk posed by the substance or by the actual preparation, its combustion products or gases discharged

Not applicable.

Protective equipment

Not applicable.

Manufacturer/Supplier: Vandex Isoliermittel-Gesellschaft mbH, D-21493 Schwarzenbek
Product number: 05
Trade name: VANDEX BB 75
Printing date: 01.03.2000

Reviewed on: 01.03.2000

Page: 002/004

06. Accidental release measures

Personal precautions

Avoid contact with skin and eyes.

Environmental precautions

Avoid uncontrolled contact with water. Avoid uncontrolled discharge into environment after contact with water. Do not allow to enter into ground water or drains after contact with water.

Methods for cleaning up/collecting

Clean up dry. Avoid dust formation.

07. Handling and storage

Information for safe handling

Store protected from humidity.

Keep out of the reach of children.

Avoid contact with skin and eyes.

Avoid dust formation and dust deposit.

Information about protection against explosions and fires

Not applicable.

Requirements to be met by storerooms and containers

Store protected from humidity in original packaging.

Information about separation of incompatible products

Not applicable.

08. Exposure controls and personal protection

Additional information about engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If this is not sufficient to maintain concentrations of particulates below the OEL, suitable respiratory protection must be worn. Avoid dust formation.

Components with critical values that require monitoring at the workplace (exposure limits)

GENERAL THRESHOLD LIMIT VALUE (Great Britain)

Specification:	Total inhalable dust	Respirable dust
Value:	10 mg/m ³	4 mg/m ³
Valid as per (mm/yy)	1999	1999

Personal protective equipment

General protective and hygiene measures

Do not eat or drink during work – no smoking. Wash hands before breaks and after work. Apply a fatty skin protection cream before work and after each break. Use skin protection products after work.

Respiratory equipment

In case of dust formation wear suitable dust mask with P2 particle filter.

Skin protection

Use suitable protective gloves.

Eye protection

Use tightly fitting safety glasses.

09. Physical and chemical properties

Image

Form: powder

Colour: grey

Odour: odourless

Relevant safety data

Change in condition

Boiling point: not applicable

Flashpoint: not applicable

Ignition temperature: not applicable

Manufacturer/Supplier: Vandex Isoliermittel-Gesellschaft mbH, D-21493 Schwarzenbek
Product number: 05
Trade name: VANDEX BB 75
Printing date: 01.03.2000

Reviewed on: 01.03.2000

Page: 003/004

Explosive limits:
Lower/Upper: not applicable
Vapor pressure: not applicable
Bulk density: approx. 1.40 kg/l
Solubility in water: (20°C) up to 1.5 g/l
pH-value: 11 – 13.5

10. Stability and reactivity

Conditions to avoid

Avoid contact with humidity.

Materials to avoid

Not applicable.

Dangerous decomposition products

Not applicable.

11. Toxicological information

Acute toxicity

There is not data available on the preparation itself.

12. Ecological information

Eco-toxicological effect: Only possible in case of unintended release of big quantities in contact with water due to increased pH value.

13. Disposal considerations

Product/Preparation

Recommendation

Clean up dry, not contaminated material can be re-used. Hardens after contact with water, hardened material can be disposed of as *construction and demolition waste* - concrete (EWC-Code 170101). The listed waste number according to the European Waste Code (EWC) is a recommendation. The final classification has to be done together with the local waste disposal company / authority.

Contaminated packaging

Recommendation

Contaminated packaging must be emptied of all residues and following appropriate cleaning can be recycled. Uncleaned packaging must be disposed of in accordance with official local regulations (EWC-Code 150105 composite packaging (Paper/PE-foil)).

14. Transport information

Not a dangerous good according to the transport regulations.

Manufacturer/Supplier: Vandex Isoliermittel-Gesellschaft mbH, D-21493 Schwarzenbek

Product number: 05

Trade name: VANDEX BB 75

Printing date: 01.03.2000

Reviewed on: 01.03.2000

Page: 004/004

15. Regulatory information

Classification according to EEC directives

Danger symbol and danger designation

Xi irritant

Hazard-determining components of labelling

Cement

Risk-phrases

R 36/38 Irritating to eyes and skin.

R 43 May cause sensitization by skin contact.

Safety-phrases

S 2 Keep out of the reach of children.

S 24/25 Avoid contact with skin and eyes.

S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 37 Wear suitable gloves.

National Regulations

16. Other information

Department issuing data specification sheet:

Technical Department

Contact

Mr. Schenk (Vandex Isoliermittel GmbH, Germany), phone 04151/89 15-0

Ms. Pridal (Vandex International AG, Switzerland), phone 033 227 44 44; from 1.7.2000: 032 626 36 36

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Manufacturer/Supplier: Vandex Isoliermittel-Gesellschaft mbH D-21493 Schwarzenbek
Product number: 150
Trade name: VANDEX CEMELAST LIQUID
Printing date: 16.06.03 Reviewed on: 16.06.03 / Version 3 Page: 001/003

01. Identification of substance, preparation and company

Trade name

VANDEX CEMELAST LIQUID

Manufacturer/Supplier

Vandex Isoliermittel-Gesellschaft m.b.H.

Street/P.O. Box

Industriestrasse 19 - 23

Country Code/Postal Code/Town/City

D-21493 Schwarzenbek

Telephone/Telefax

Phone: +49 (0) 4151 89 15-0

Fax: +49 (0) 4151 89 15 50

Emergency Information

Phone: +49 (0) 4151 89 15 31

(Laboratory, Vandex Isoliermittel GmbH, Germany)

Phone: +41 (0) 32 626 36 36

(Mrs. Ch. Pridal, Vandex International Ltd, Switzerland)

02. Composition/Information on components

Chemical characterization

Chemical nature :

Water based dispersion of butadiene styrene copolymer

Hazardous components:

none according to EU directive 1999/45/EC

03. Hazards identification

Critical hazards to man and the environment: none according to EU directive 1999/45/EC

04. First aid measures

Inhalation of vapour

Remove to fresh air. In severe cases seek medical attention

Skin contact

Prolonged contact may cause irritation. Remove contaminated clothing. Wash thoroughly with soap and water. Seek medical attention if symptoms persist

Eye contact

May cause temporary irritation. Irrigate with water for minutes holding eyelid open.

Ingestion

May cause nausea. Seek immediate medical attention. Do not induce vomiting.

05. Fire-fighting measures

The product is water based and is not combustible.

06. Accidental release measures

Personal precautions

Refer to Section 8.

Environmental precautions

Prevent product entering soil, natural waters and drains.

Methods for cleaning up/collecting

Large spillages should be contained and pumped into a receiving vessel. Small spillages should be absorbed on inert absorbant. For disposal methods refer to Section 13.

07. Handling and storage

Information for safe handling

No special precautions necessary. Observe good housekeeping practice. Keep workplace well ventilated.

Information for safe storage

Store between +5°C and +35°C protected from frost and direct sunlight. Do not use storage vessels or pipework made of aluminium.

Manufacturer/Supplier: Vandex Isoliermittel-Gesellschaft mbH D-21493 Schwarzenbek
Product number: 150
Trade name: VANDEX CEMELAST LIQUID
Printing date: 16.06.03
Reviewed on: 16.06.03 / Version 3 Page: 002/003

08. Exposure controls and personal protection

General protective measures

The product may contain low levels of volatile organic compounds or ammonia which may evaporate during application and drying.

Advice on system design

Provide good general ventilation in the workplace. Where the product is dried or sprayed, local extraction is recommended.

Components with workplace parameters

None according to EU directive 88/379/EC

Personal protective equipment

Respiratory protection

If spraying product without local exhaust ventilation, wear a normal dust mask.

Hand protection

Impermeable gloves recommended

Eye protection

Eye protection recommended

Skin protection

In case of severe splashing wear waterproof overalls and boots. Wash with soap and water after handling

Hygiene measures

Do not eat, drink or smoke when handling product.

09. Physical and chemical properties

Image

Form: liquid
Colour: white
Odour: faint aromatic

Relevant safety data

Vapor pressure:	approx. 23 hPa (water) at 20°C
Relative density:	0.9 – 1.1
Solubility in water:	insoluble, but miscible in all proportions
pH-value:	9.0 – 10.0
Viscosity:	100 – 1000 mPa·s

10. Stability and reactivity

The product is stable under recommended storage conditions. (Section 7)

Incompatible materials : none

11. Toxicological information

Long term experience of this product type indicates no danger to health when properly handled under industrial conditions.

12. Ecological information

Degradation / elimination:	DOC elimination after 2 days (OECD302B) : 98%. The product can be virtually eliminated from water by abiotic processes, e.g. adsorption onto activated sludge
Bioaccumulation:	No evidence for bioaccumulation
Ecotoxic effects:	The product is not classified as Dangerous for the Environment

13. Disposal considerations

Product/Preparation

Recommendation

Waste product should not be discharged directly into drains or waterways without treatment. Disposal of product and packaging should always comply with local and national regulations. Waste water containing product should be treated in a separation and biological treatment plant.

EU Waste code number : No Waste Code Number available

Manufacturer/Supplier: Vandex Isoliermittel-Gesellschaft mbH D-21493 Schwarzenbek
Product number: 150
Trade name: VANDEX CEMELAST LIQUID
Printing date: 16.06.03 Reviewed on: 16.06.03 / Version 3 Page: 003/003

14. Transport information

The product is not classified as Dangerous for Carriage.

15. Regulatory information

Labelling according to EU directive 1999/45/EC:

Symbol Not subject to labelling

National regulations:

Germany : Water hazard class WGK = 1, VwVwS, Kenn. Nr. 662

Information given in this Material Safety Data Sheet does not constitute the user's own workplace risk assessment

16. Other information

Department issuing data specification sheet:

Technical Department

Contact

Mr. Schenk (Vandex Isoliermittel G.m.b.H., Germany) phone: 04151 / 89 15-0

Ms. Pridal (Vandex International AG, Switzerland) phone: +41 (0) 32 626 36 36

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
